

ND – NON-METALLIC (ARAMID) DOUBLE EYE CABLE SOCKS

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ Continuous weave configuration
- ✓ No fraying wires
- ✓ Lighter and safer to handle
- ✓ Longer life

Ideal for fibre optic applications, offshore or for a multitude of uses in the electrical industry; dramatically improved weight to break ratio. Slingco's non-metallic pulling socks are made of a high-strength, non-metallic aramid fiber, with UV protective coating; they are suitable for pulling both single cable and cable bundles. These woven mesh cable socks offer a non-metallic alternative to steel. Non-metallic material is easy to work with even without gloves.

Double Eye Single Weave Non-Metallic Sock

| Slingco Part No. | Range (mm) | Range (in) | Lattice Length (mm) | Lattice Length (in) | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------|------------|-------------|---------------------|---------------------|-------------------------|-------------------------|
| ZCS1148 | 10 - 20 | 0.38 - 0.75 | 552 | 22 | 1,115 | 2,460 |
| ZCS1176 | 20 - 30 | 0.75 - 1.25 | 523 | 21 | 1,620 | 3,580 |
| ZCS2922 | 25 - 38 | 1.00 - 1.50 | 573 | 23 | 1,620 | 3,580 |
| ZCS1177 | 30 - 40 | 1.25 - 1.50 | 642 | 25 | 2,230 | 4,920 |
| ZCS1178 | 40 - 50 | 1.50 - 2.00 | 487 | 19 | 2,640 | 5,820 |

Double Eye Double Weave Non-Metallic Sock

| Slingco Part No. | Range (mm) | Range (in) | Lattice Length (mm) | Lattice Length (in) | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------|------------|-------------|---------------------|---------------------|-------------------------|-------------------------|
| ZCS1182 | 30 - 40 | 1.25 - 1.50 | 642 | 25 | 4,472 | 9,860 |
| ZCS1183 | 40 - 50 | 1.50 - 2.00 | 667 | 26 | 5389 | 11,880 |
| ZCS1184 | 50 - 65 | 2.00 - 2.50 | 636 | 25 | 7,212 | 15,900 |
| ZCS1185 | 65 - 76 | 2.50 - 3.00 | 762 | 30 | 7,212 | 15,900 |
| ZCS1186 | 76 - 102 | 3.00 - 4.00 | 800 | 32 | 7,212 | 15,900 |
| ZCS3813 | 102 - 127 | 4.00 - 5.00 | 1,540 | 61 | 7,212 | 15,900 |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au