

# NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE SOCK

## **⚠ WARNING**

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Continuous weave configuration
- ✓ No fraying wires
- ✓ Lighter and safer to handle
- ✓ Longer Life

Ideal for fibre optic applications, offshore or for a multitude of uses in the electrical industry; dramatically improved weight to break ratio. Slingco's non-metallic pulling socks are made of a high-strength, non-metallic aramid fibre, with UV protective coating; they are suitable for pulling both single cable and cable bundles. These woven mesh grips offer a non-metallic alternative to steel. Non-metallic material is easy to work with even without gloves.

### Single Eye Single Weave Non-Metallic Sock

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS1040	10 - 20	0.38 - 0.75	552	21	1,115	2,460
ZCS1022	20 - 30	0.75 - 1.25	523	21	1,620	3,580
ZCS2923	25 - 38	1.00 - 1.50	573	23	1,620	3,580
ZCS1041	30 - 40	1.25 - 1.50	642	25	2,230	4,920
ZCS1042	40 - 50	1.50 - 2.00	485	19	2,640	5,820

### Single Eye Double Weave Non-Metallic Sock

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS1023	30 - 40	1.25 - 1.50	642	25	4,470	9,860
ZCS1024	40 - 50	1.50 - 2.00	523	21	5,390	11,880
ZCS1179	50 - 65	2.00 - 2.50	636	25	7,210	15,900
ZCS1180	65 - 76	2.50 - 3.00	908	36	7,210	15,900
ZCS1181	76 - 102	3.00 - 4.00	1,029	40	7,210	15,900
	100 - 125		3,168		7,210	

### Single Eye Double Weave High Strength Non-Metallic Sock

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS13054		4.00 - 5.00		118		45,500

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

#### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au

## NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE SOCK

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

### GET IN TOUCH



+61 3 8840 6556



[sales@slingcoaustralia.com.au](mailto:sales@slingcoaustralia.com.au)