

# SWIVEL & CONNECTOR REPLACEMENT PINS

## **⚠ WARNING**

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Pins to suit our connector link
- ✓ High Strength

Replacement pins for the popular connectors.

Swivel or Connector Model	Replacement Pin (HEX)
ZSW2091, ZSW6554	SWI2859
ZSW2092	SWI2810
ZSW2093, ZSW6555	SWI2339
ZSW2094	SWI2341
ZSW6122	SWI2343
ZSW2096	SWI4079
ZSW2097	SWI2344
ZSW2929	SWI2801
ZSW2649	SWI2648
ZSW2857	SWI2748
ZSW6123	SWI5184
ZSW6556	SWI5309
ZSW6557, ZSW6558, ZSW6559, ZSW6560	SWI5310

### Note

All Slingco Line Pulling Swivels are designed for straight line pulling and will not support side loads as would be encountered traveling over a bull wheel. Swivel selection should be based on pulling line diameter, grip size, opening dimensions, pin sizes, working load, and sheave groove diameter. Swivels are not designed for general lifting.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH



+61 3 8840 6556



[sales@slingcoaustralia.com.au](mailto:sales@slingcoaustralia.com.au)