

# DOUBLE EYE SPLIT MESH LACE CLOSING SUPPORT SOCKS

## ⚠️ WARNING

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for two connect/support points
- ✓ Use when the end of the cable is not accessible

Double eye split mesh lace closing, in 304 Stainless Steel, for secure attachment and support where the cable end is not accessible.

Slingco Part No.	Approx. Break Load (lb)	Approx. Break Load (kg)	Lattice Length (in)	Lattice Length (mm)	Lattice Material	Range (in)	Range (mm)
ZCS2998	530	240	10	254	304 Stainless	0.50 - 0.63	12 - 16
ZCS2999	790	360	10	254	304 Stainless	0.63 - .0.75	16 - 19
ZCS3000	1,020	460	13	330	304 Stainless	0.75 - 1.00	19 - 25
ZCS3001	1,610	730	14	355	304 Stainless	1.00 - 1.25	25 - 31
ZCS3002	1,610	730	15	381	304 Stainless	1.25 - 1.50	31 - 38
ZCS3003	1,610	730	17	432	304 Stainless	1.50 - 1.75	38 - 44
ZCS3004	2,150	975	19	482	304 Stainless	1.75 - 2.00	44 - 50
ZCS3005	3,260	1,480	21	533	304 Stainless	2.00 - 2.50	50 - 63
ZCS3006	3,260	1,480	23	584	304 Stainless	2.50 - 3.00	63 - 76
ZCS3007	4,900	2,222	25	635	304 Stainless	3.00 - 3.50	76 - 89
ZCS3008	4,900	2,222	27	685	304 Stainless	3.50 - 4.00	89 - 102

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au


# DOUBLE EYE SPLIT MESH LACE CLOSING SUPPORT SOCKS

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH

 +61 3 8840 6556

 [sales@slingcoaustralia.com.au](mailto:sales@slingcoaustralia.com.au)