

# REEL LIFTER

## ⚠ WARNING

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Rugged construction to lift and unpend reels
- ✓ Easy rotation to unroll cable
- ✓ Counterweighted bottom arm for easy insertion in reel
- ✓ Side flipping eye allows reels to be put into a non-rolling position
- ✓ Complies with ASME B30.20.1

Makes handling large cable reels quick and easy, on-site or in warehouses.

The Slingco Reel Lifter is a high capacity, compact unit that allows users in the utility construction industry to safely load, transport, and dispense wire and/or cable on-site. It is also used in many industrial applications to make moving and relocating reels in a warehouse easy. Now a task that normally used a team of three or four people can be done with just one, allowing the crew to operate more efficiently!

[Download our Reel Lifter leaflet.](#)

Slingco Part No.	Arbor Hole Min. (ins)	Arbor Hole Max. (ins)	Capacity (lb)	Weight (lb)	Length (ins)
ZLD08729	2	4	3,000	6.50	16 1/8
ZLD09186	3	6	5,000	14.50	21 1/8
ZLD10807	3.25	6	12,000	32.33	30.53

## Slingco Part Description No.

ZLD09708 3,000lb factory repair kit with extension springs, cable assemblies and all necessary pins for replacement of the interior cable system. Suitable for ZLD08729.

ZLD09707 5,000lb factory repair kit with extension springs, cable assemblies and all necessary pins for replacement of the interior cable system. Suitable for ZLD09186.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH



+61 3 8840 6556



[sales@slingcoaustralia.com.au](mailto:sales@slingcoaustralia.com.au)