

# HAND LINE BLOCK (3")

## **⚠ WARNING**

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ 3" nylon fiberglass block with 1,000 lb Safe Working Load limit
- ✓ Side opening feature allows quick access to remove the hand line

Slingco's Hand Line Tools feature a 76.2mm (3") nylon fiberglass block, with a safe working load limit of 453.59 kg (1,000 lb).

Our 76.2mm (3") Hand Line Block's sheave can accommodate a 15.875 mm (0.625") diameter rope, and operates smoothly on the 12.7 mm (0.5") diameter axle and swivel bearings. The side opening feature allows quick access to remove the hand line.

Slingco Part No.	Description	Working Load Limit (lb)	Working Load Limit (kg)
ZAB8725	3" Hand Line Block (Screw Pin)	1,000	453.59
ZAB8725-P	3" Hand Line Block (Push Pin)	1,000	453.59
ZAB8725-M	3" Hand Line Block (with Meat Hook)	1,000	453.59

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH

+61 3 8840 6556

[sales@slingcoaustralia.com.au](mailto:sales@slingcoaustralia.com.au)