

POLE STAND



KEY FEATURES

- ✓ Lightweight and compact
- ✓ Quick swing-and-lock legs
- ✓ Positions poles for safe and comfortable framing
- ✓ 6,000 lbs. capacity

Slingco's pole stand is lightweight and compact making it easy to place, remove, and store on your truck or jobsite. The support leg's swing-and-lock design make moving and storing the Slingco pole stand a breeze.

The pole stand positions the pole at an optimal height for easy and safe framing.

The pole stand's capacity of 6,000 lb makes it capable of handling the majority of wood distribution poles. Its curved cradle allows for safe rotation of the pole for proper framing positioning.

The pole stand's high visibility and durability make it a proven choice for any work location or environment.

Slingco Part No.	Capacity (lbs)	Capacity (kgs)	Height (in)	Height (cm)	Width (in)	Width (cm)	Weight (lbs)	Weight (kgs)
TPE09682	9,000	4,082	23.75	60.33	30	76.2	32	14.5
TPE13932	12,500	5,670	23.18	58.88	30.6	12	34.6	15.7

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

GET IN TOUCH



+61 3 8840 6556



sales@slingcoaustralia.com.au