

# 10K DRIVE WRENCH ASSEMBLY



## KEY FEATURES


- ✓ System Component Options:
- ✓ Orange Drive Wrench (#SAE09639)
- ✓ Yellow Drive Wrench (#SAE08666)
- ✓ Square Shank Anchor Tool (#SAE11132)
- ✓ Drive Wrench Lock (#SAE10425)
- ✓ Square Drive Head Adapter (#SAE14309)
- ✓ 2.625 in Hex Kelly Bar Adapter (#SAE10427)
- ✓ 1.5 in Square Shank Bolted Assembly (#SAE13513)

Slingco's 10k Drive Wrench Assembly is a tool system for the installation of screw anchors.

Designed to connect the square anchor of a drive motor or screw anchor to the hexagonal Kelly Bar of a bucket truck. System options include Drive Wrenches to suit different sized anchor rods; a Drive Wrench lock; two Kelly Bar Adapters to fit the hex drive bar's dimensions (2.5 in and 2.625 in) and one Square Head Kelly Bar Adapter to suit 3 in Square Drive Bar.

The Drive Wrench Lock attaches to the Kelly Bar Adapter and makes the installation of the Anchor Rod much easier. The three position rings of the lock assembly ensure easy capture of the Drive Wrench and Anchor Rod, holding them securely while under torque and releasing them when needed.

The Drive Wrenches are designed to allow Anchor Rods to telescope inside, and secure to, the Drive Wrench Lock. The Drive Wrench transfers the torque from the Drive motor to the Screw Anchor, and are rated to 10,000 ft-lb.




## GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au

# 10K DRIVE WRENCH ASSEMBLY



## GET IN TOUCH

# 10K DRIVE WRENCH ASSEMBLY

Slingco Part No.	Kelly Bar Shape	X mm (in)	Y mm (in)	Z mm (in)	Weight each kg (lb)
SAE10486	HEX	63.5 (2.5)	108 (4.25)	210 (8.25)	7.39 (16.3)
SAE10427	HEX	66.7 (2.625)	108 (4.25)	210 (8.25)	7.57 (16.7)

Slingco Part No.	Kelly Bar Shape	Description	X mm (in)	Y mm (in)	Weight kg (lb)
SAE14309	SQU	76 x 76 mm Square Head Adapter	76 (3)	240 (9.4)	7.5 (16.5)

Slingco Part No.	Description	Height mm (in)	Weight kg (lb)
SAE10425	Drive Lock Assembly	7.5 (190.5)	8.35 (18.4)
SAE13513	1-1/2" Square Shank Bolted Assembly		

Slingco Part No.	Description	Hub Size mm (in)	Shaft Size mm (in)
SAE09639	10,000ft-lb Orange Drive Wrench	57 (2.25)	35 (1.375)
SAE08666	10,000ft-lb Yellow Drive Wrench	63.5 (2.5)	38 (1.5)

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

## GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au