

TRI & QUAD PULLING SLINGS

⚠ WARNING


Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ For simultaneous pulling multiple conductors
- ✓ Helps to minimise the size of the pulling bundle
- ✓ Available in 3 or 4 leg versions

This staggered pulling sling is designed to allow the pulling of multiple conductors at the same time while minimising the overall diameter of your pulling bundle. Pulling slings come in three leg or four leg versions. Use a swivel for each leg and at the head of the sling to release torsion, allowing conductors to rotate freely. Suggested swivels are listed with each model.



GET IN TOUCH

01706 855 558

sales@slingco.com

TRI & QUAD PULLING SLINGS

Slingco Part No.	Leg 1 Length (mm)	Leg 1 Length (in)	Leg 2 Length (mm)	Leg 2 Length (in)	Leg 3 Length (mm)	Leg 3 Length (in)	Leg 4 Length (mm)	Leg 4 Length (in)	Head of Sling Swivel Suggestion	Leg Swivel Suggestion
ZSH2264	520	20.5	880	34.65	1,340	52.75	n/a	n/a	ZSW2092	ZSW2091
ZSH2265	520	20.5	880	34.65	1,340	52.75	1,760	69.3	ZSW2092	ZSW2092

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

01706 855 558

sales@slingco.com