

SINGLE EYE SPLIT MESH LACE CLOSING SUPPORT GRIPS



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for use when the end of the cable is not accessible

In 304 stainless steel. Split mesh is for when end of cable is not available.

Slingco Part No.	Approx. Break Load (lb)	Approx. Break Load (kg)	Lattice Length (in)	Lattice Length (mm)	Range (in)	Range (mm)
ZCS1904	567	255	9.7	247	0.50 - 0.63	12 - 16
ZCS1905	890	358	9.7	247	0.63 - .0.75	16 - 19
ZCS1906	1,040	470	13	331	0.75 - 1.00	19 - 25
ZCS1907	1,700	770	13.5	344	1.00 - 1.25	25 - 31
ZCS1908	1,700	770	15	382	1.25 - 1.50	31 - 38
ZCS1909	1,700	770	16.5	420	1.50 - 1.75	38- -44
ZCS1910	2,300	1,040	20	509	1.75 - 2.00	44 - 50
ZCS1911	3,400	1,540	21	535	2.00 - 2.50	50 - 63
ZCS1912	3,400	1,540	24	611	2.50 - 3.00	63 - 76
ZCS1913	5,000	2,265	26	662	3.00 - 3.50	76 - 89
ZCS1914	5,000	2,265	29	738	3.50 - 4.00	89 - 102

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

01706 855 558

sales@slingco.com