

UNIVERSAL EYE CLOSED MESH CABLE SUPPORT GRIPS

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed with adjustable universal eye

Fitted with an adjustable eye for easy and secure attachment, where the end of the cable can be inserted in to the support grip. Made from 304 Stainless Steel.

Slingco Part No.	Approx. Break Load (lb)	Approx. Break Load (kg)	Lattice Length (in)	Lattice Length (mm)	Range (in)	Range (mm)
ZCS2664	530	240	10	254	0.50 - 0.63	12 - 16
ZCS2665	790	360	10	254	0.63 - 0.75	16 - 19
ZCS2666	1,020	460	13	330	0.75 - 1.00	19 - 25
ZCS2667	1,610	730	14	355	1.00 - 1.25	25 - 31
ZCS2324	1,610	730	15	381	1.25 - 1.50	31 - 38
ZCS2668	1,610	730	17	432	1.50 - 1.75	38 - 44
ZCS2669	2,150	975	19	483	1.75 - 2.00	44 - 50
ZCS2670	3,260	1,480	21	533	2.00 - 2.50	50 - 63
ZCS2671	3,260	1,480	23	584	2.50 - 3.00	63 - 76

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com