

SINGLE EYE DOUBLE WEAVE PULLING GRIP

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ Flexible eye
- ✓ Double weave mesh
- ✓ 600mm & 900mm lengths
- ✓ Available in DOUBLE EYE

Flex eye general duty pulling grips. Made of galvanised wire these grips in 600mm and 900mm lengths are perfect for general light to medium duty pulling applications.



600 mm Series

Slingco Part No.	Range (mm)	Lattice Weave	Lattice Length (mm)	Overall Length (mm)	Approx. Break Load (kg)
ZCS12627	6 - 10	Double	600	886	1504
ZCS12628	10 - 20	Double	600	886	1,860
ZCS12629	20 - 30	Double	600	886	2,256
ZCS12630	30 - 40	Double	600	886	3,696
ZCS12631	40 - 50	Double	600	895	5,490
ZCS12632	50 - 65	Double	600	895	5,490
ZCS12633	65 - 80	Double	600	895	7,320
ZCS12634	80 - 95	Double	600	895	7,320
ZCS12635	95 - 110	Double	600	895	10,613
ZCS12636	110 - 130	Double	600	895	10,613
ZCS12637	130 - 150	Double	600	904	10,613

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

SINGLE EYE DOUBLE WEAVE PULLING GRIP

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

 01706 855 558

 sales@slingco.com