

# POLE CLAMP

## ⚠️ WARNING

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Unique handle lock system for easier installation
- ✓ Made of ultraviolet stabilized fiberglass-reinforced polymer
- ✓ Two sizes

Slingco Pole Clamps are used to hold insulating blankets and other types of cover-ups in place while performing work and is constructed of ultraviolet stabilized fiberglass-reinforced polymer.

Slingco's Pole Clamps are meant to eliminate the use of tie wraps, bungee cords, tapes or any other items that can cause damage to insulated rubber products.

With Slingco's unique tool handle lock system, the Pole Clamp can be set in an open position by engaging the handle lock. Once the product is in its intended location the lock can be released making installation easier.



Slingco Part No.	Length (in)	Length (mm)	Width (in)	Width (mm)	Jaw Opening (in)	Jaw Opening (mm)	Weight (lbs)	Weight (kg)
ZPE11399	20.25	514.4	8.25	203.2	13.5	342.9	1.7	0.77
ZPE11398	28	711.2	11.5	291.2	19.75	501.7	2.2	1.0

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



## GET IN TOUCH

☎ 01706 855 558

✉ [sales@slingco.com](mailto:sales@slingco.com)