

STANDARD DUTY HOSE RESTRAINT GRIPS - DOUBLE EYE



KEY FEATURES

- ✓ Prevent whipping in the event of a pressurised hose becoming detached from its fitting
- ✓ Made from the highest grade galvanised steel and 316 stainless steel wire
- ✓ Colour coded for easy range identification

Slingco offer a range of safety restraining grips and whipchecks designed to prevent whipping in the event of a pressurised hose becoming detached from its fitting.

Made from the highest grade galvanised steel and 316 stainless steel wire, and colour coded for range identification, our grips are designed for various plant-critical applications across a wide range of commercial industries. Suitable for restraining all types of high pressure hoses such as water and air hoses, hydraulic hoses, concrete pump and delivery hoses as well as supporting electrical cabling within critical applications within mining, automation and other industrial sectors.

The grips are woven in such a way that the lattice or weave is uniform throughout its length, ensuring even load protection around the hose. This helps with any adverse abrasion to the hose and prevents displacement in the event of rupture. Available for 5mm to 200mm diameter hoses.



GET IN TOUCH

01706 855 558

sales@slingco.com

STANDARD DUTY HOSE RESTRAINT GRIPS - DOUBLE EYE

Metric

Standard Duty Hose Restraints

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave Range (mm)	Eye Length (mm)	Lattice/Weave (mm)	Overall length (mm)	Break load (kg)	Break load (kN)	Colour code
ZCS14350	Galv	SS	6	Double 6-14	90	330	420	1600	16	White
ZCS14351	Galv	SS	6	Double 14-20	90	352	442	2000	20	White
ZCS14352	Galv	SS	6	Double 20-30	115	574	689	2500	25	White
ZCS14353	Galv	SS	8	Double 30-40	165	810	975	4300	42	Brown
ZCS14354	Galv	SS	8	Double 40-50	185	893	1078	6200	61	Orange
ZCS14355	Galv	SS	10	Double 50-60	230	1215	1445	8100	79	Yellow
ZCS14356	Galv	SS	10	Double 60-70	240	1224	1464	8100	79	Blue
ZCS14357	Galv	SS	10	Double 70-90	260	1295	1555	8100	79	Red
ZCS14358	Galv	SS	14	Double 90-110	280	1468	1748	10500	103	Green
ZCS14359	Galv	SS	14	Double 110-130	350	1551	1901	12500	123	Black
ZCS14360	Galv	SS	16	Double 120-150	400	1582	1982	16000	157	Grey
ZCS14361	Galv	SS	16	Double 140-180	450	1533	1983	20000	196	Light Blue
ZCS14362	SS	SS	6	Double 6-14	90	330	420	1280	13	White
ZCS14363	SS	SS	6	Double 14-20	90	352	442	1600	16	White
ZCS14364	SS	SS	6	Double 20-30	115	574	689	2000	20	White
ZCS14365	SS	SS	8	Double 30-40	165	810	975	3440	34	Brown
ZCS14366	SS	SS	8	Double 40-50	185	893	1078	4960	49	Orange
ZCS14367	SS	SS	10	Double 50-60	230	1215	1445	6480	64	Yellow
ZCS14368	SS	SS	10	Double 60-70	240	1224	1464	6480	64	Blue
ZCS14369	SS	SS	10	Double 70-90	260	1295	1555	6480	64	Red
ZCS14370	SS	SS	14	Double 90-110	280	1468	1748	8400	82	Green

Metric

Wide-Range Restraint

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave Range (mm)	Eye Length (mm)	Lattice/Weave (mm)	Overall length (mm)	Break load (kg)	Break load (kN)	Colour code
ZCS14347	Galv	N/A	N/A	Double 50-120	306	594	900	5080	50	ZCS14347



GET IN TOUCH

01706 855 558

sales@slingco.com

STANDARD DUTY HOSE RESTRAINT GRIPS - DOUBLE EYE

Imperial

Standard Duty Hose Restraints

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave	Range (in)	Eye Length (in)	Lattice/Weave (in)	Overall Length (in)	Break Load (lb)	Colour code
ZCS14350	Galv	SS	6	Double	0.24-0.55	4	13	17	3,527	White
ZCS14351	Galv	SS	6	Double	0.55-0.80	4	14	17	4,409	White
ZCS14352	Galv	SS	6	Double	0.80-1.25	5	23	27	5,512	White
ZCS14353	Galv	SS	8	Double	1.25-1.50	6	32	38	9,480	Brown
ZCS14354	Galv	SS	8	Double	1.50-2.00	7	35	42	13,669	Orange
ZCS14355	Galv	SS	10	Double	2.00-2.40	9	48	57	17,857	Yellow
ZCS14356	Galv	SS	10	Double	2.40-2.75	9	48	58	17,857	Blue
ZCS14357	Galv	SS	10	Double	2.75-3.50	10	51	61	17,857	Red
ZCS14358	Galv	SS	14	Double	3.50-4.30	11	58	69	23,148	Green
ZCS14359	Galv	SS	14	Double	4.30-5.00	14	61	75	27,558	Black
ZCS14360	Galv	SS	16	Double	4.70-5.90	16	62	78	35,274	Grey
ZCS14361	Galv	SS	16	Double	5.50-7.00	18	60	78	44,092	Light Blue
ZCS14362	SS	SS	6	Double	0.24-0.55	4	13	17	2,822	White
ZCS14363	SS	SS	6	Double	0.55-0.80	4	14	17	3,527	White
ZCS14364	SS	SS	6	Double	0.80-1.25	5	23	27	4,409	White
ZCS14365	SS	SS	8	Double	1.25-1.50	6	32	38	7,584	Brown
ZCS14366	SS	SS	8	Double	1.50-2.00	7	35	42	10,935	Orange
ZCS14367	SS	SS	10	Double	2.00-2.40	9	48	57	14,286	Yellow
ZCS14368	SS	SS	10	Double	2.40-2.75	9	48	58	14,286	Blue
ZCS14369	SS	SS	10	Double	2.75-3.50	10	51	61	14,286	Red
ZCS14370	SS	SS	14	Double	3.50-4.30	11	58	69	18,519	Green

Imperial

Wide-Range Restraint

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave	Range (in)	Eye Length (in)	Lattice/Weave (in)	Overall Length (in)	Break Load (lb)	Colour code
ZCS14347	Galv	N/A	N/A	Double	2.00-4.72	12	23.4	900	11,200	-



GET IN TOUCH

01706 855 558

sales@slingco.com

STANDARD DUTY HOSE RESTRAINT GRIPS - DOUBLE EYE

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478