

# BOLT CUTTERS

## **⚠ WARNING**

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Superior cutting performance
- ✓ Ergonomic comfort
- ✓ Fiberglass and steel handles
- ✓ Available in 18", 24", 30" and 36" lengths
- ✓ Versatile application for hard and soft materials

When your work calls for a reliable, powerful cutting tool, turn to Slingco Bolt Cutters. Designed and built for the demanding, daily use of utility professionals and contractors, these cutters deliver consistent performance.

Our hardened steel blades provide clean, powerful cuts across a wide variety of materials, including soft metals, chain, and rebar. The ergonomic handles are engineered for optimal grip and leverage, which helps reduce operator fatigue and improves control during tough applications.

With a variety of sizes available, Slingco has the right tool for the job, helping you work efficiently and safely.

**WARNING: DO NOT** use on energized lines.

Material	Slingco Part No.	Part No. Suffix/Length (in)	Hard Cut Capacity (HRC 48)	Soft/Medium Cut Capacity (HRC 19)	Weight
Steel	TCU15812	-18	9/32" (7 mm)	3/8" (10 mm)	3.4 lb (1.5 kg)
Steel	TCU15812	-24	5/16" (8 mm)	7/16" (11 mm)	5.3 lb (2.4 kg)
Steel	TCU15812	-30	3/8" (10 mm)	1/2" (13 mm)	8.4 lb (3.8 kg)
Steel	TCU15812	-36	7/16" (11 mm)	9/16" (14 mm)	11.3 lb (5.1 kg)
Fiberglass	TCU15813	-18	9/32" (7 mm)	3/8" (10 mm)	3.4 lb (1.5 kg)
Fiberglass	TCU15813	-24	5/16" (8 mm)	7/16" (11 mm)	5.2 lb (2.35 kg)
Fiberglass	TCU15813	-30	3/8" (10 mm)	1/2" (13 mm)	8.5 lb (3.85 kg)
Fiberglass	TCU15813	-36	7/16" (11 mm)	9/16" (14 mm)	11.6 lb (5.26 kg)



## GET IN TOUCH

01706 855 558

sales@slingco.com

# BOLT CUTTERS

## Replacement Parts for Slingco Bolt Cutters

Slingco Part No.	Description
TCU16213	18" Bolt Cutter Replacement Head (w/ mounting hardware)
TCU16214	24" Bolt Cutter Replacement Head (w/ mounting hardware)
TCU16215	30" Bolt Cutter Replacement Head (w/ mounting hardware)
TCU16216	36" Bolt Cutter Replacement Head (w/ mounting hardware)
TCU16257	18" Mounting Hardware (3x Bolt and Nut)
TCU16258	24" Mounting Hardware (3x Bolt and Nut)
TCU16259	30" Mounting Hardware (3x Bolt and Nut)
TCU16260	36" Mounting Hardware (3x Bolt and Nut)
TCU16254	18" Adjustment Bolt (Pack of 5)
TCU16255	24" and 30" Adjustment Bolt (Pack of 5)
TCU16256	36" Adjustment Bolt (Pack of 5)

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



### GET IN TOUCH

 01706 855 558

 sales@slingco.com