

35KV JUMPER CLAMP

LIGHTWEIGHT, IMPACT RESISTANT AND INCREDIBLY DURABLE



ZSC09344 Jumper Clamp meets ASTM F2321

Slingco's Jumper Clamps are used as a part of jumper cable assemblies to bypass work areas when equipment is under repair or being upgraded.

Jumper clamps are lightweight and impact resistant making them incredibly durable.

We make inspection of the cable, ferrule, and clamp simple and easy via the transparent clamp body.

The jaw of the Slingco Jumper Clamp and floating ring contact is made from a copper-based alloy.



Slingco Part No	Line Range	Max. Continuous Amps	Threading	Length	Weight
ZSC09344	954 MCM (0.162 - 1.25)	400	5/8" - 11 threads/inch	11.5" (292mm)	2.5 lbs (1.15 kg)
ZSC12110	477 MCM (0.162 - 0.9)	400	5/8" - 11 threads/inch	11.5" (292mm)	2.4 lbs (1.09 kg)

NOTE: Slingco Jumper Clamps are sold individually. Slingco Jumper Clamps meet ASTM F2321 standard.

WARNING

Cancer and Reproductive Harm
www.P65Warnings.ca.gov

FOR ANY ENQUIRIES CALL TODAY ON
+44 [0]1706 855558

Slingco Limited

Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG, England
 Tel: +44 [0]1706 855558 · sales@slingco.com



slingco.com