

SERVICE DROP GRIPS



KEY FEATURES

- ✓ Support cables in manufacturing, industrial and open space environments
- ✓ Extended eye makes facilitates installation at connection points
- ✓ Available in Galvanized or 304 Stainless Steel wire

Use these grips to support cables in manufacturing, industrial and open space environments. The extended eye allows for easy installation and hanging from conveniently placed connection points. Also great for Control room and wire to rack applications.

Slingco Part No.	Range (mm)	Range (in)	Wire Material	Eye Length (mm)	Eye length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS7684	5.6 - 8.1	0.22 - 0.32	Galvanized	229	9	499	1,100
ZCS7685	7.6 - 10.9	0.30 - 0.43	Galvanized	229	9	499	1,100
ZCS7686	10.4 - 14.2	0.41 - 0.56	Galvanized	229	9	499	1,100
ZCS7687	13.5 - 18.5	0.53 - 0.73	Galvanized	229	9	499	1,100
ZCS7688	17.8 - 21.6	0.70 - 0.85	Galvanized	229	9	861	1,900
ZCS7689	20.8 - 25.4	0.82 - 1.00	Galvanized	229	9	861	1,900
ZCS7690	24.4 - 31.7	0.96 - 1.25	Galvanized	178	7	861	1,900
ZCS09733	5.6 - 8.1	0.22 - 0.32	304 Stainless Steel	229	9	294	650
ZCS09734	7.6 - 10.9	0.30 - 0.43	304 Stainless Steel	229	9	499	1,100
ZCS09735	10.4 - 14.2	0.41 - 0.56	304 Stainless Steel	229	9	499	1,100
ZCS09736	13.5 - 18.5	0.53 - 0.73	304 Stainless Steel	229	9	499	1,100
ZCS09737	17.8 - 21.6	0.70 - 0.85	304 Stainless Steel	229	9	861	1,900
ZCS09738	20.8 - 25.4	0.82 - 1.00	304 Stainless Steel	229	9	861	1,900
ZCS09739	24.4 - 31.7	0.96 - 1.25	304 Stainless Steel	178	7	861	1,900



GET IN TOUCH

1 888 685 9478
sales@slingcoamerica.com

SERVICE DROP GRIPS

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH



1 888 685 9478



sales@slingcoamerica.com