

MARINE CABLE GRIPS - LACE UP



KEY FEATURES

- ✓ Bespoke design available
- ✓ Single, double, triple and quadruple weave depending upon requirement
- ✓ Thimble eye optional

These specialty grips, also called chinese fingers, are extremely heavy duty and suitable for large underwater pulling applications, plus others within the oil and gas industry. Galvanised steel construction for heavy duty pulling such as array, export, umbilicals and other underwater cable installations. Sizes cover cables ranging from 3.5" to over 14" diameters. Manufactured to order.



GET IN TOUCH



1 888 685 9478



sales@slingcoamerica.com

MARINE CABLE GRIPS - LACE UP

| Slingco Part No. FLEX Eye | Slingco Part No. THIMBLE Eye | Range (mm) | Range (in) | Lattice Length (mm) | Lattice Length (in) | Lattice Material | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------------------|---------------------------------|---------------|-----------------|------------------------|------------------------|---------------------|----------------------------|----------------------------|
| ZCS12760 | ZCS12760-THI | 90 - 125 | 3.5 - 5 | 2,000 | 78.75 | Galv | 50,000 | 110,230 |
| ZCS3545 | ZCS3545-THI | 102 - 127 | 4 - 5 | 2,005 | 78.75 | Galv | 48,000 | 105,822 |
| ZCS12761 | ZCS12761-THI | 110 - 145 | 4.3 - 5.7 | 2,500 | 98.5 | Galv | 50,000 | 110,230 |
| ZCS3546 | ZCS3546-THI | 127 - 152 | 5 - 6 | 1,821 | 71.7 | Galv | 48,000 | 105,822 |
| ZCS12762 | ZCS12762-THI | 130 - 172 | 5.1 - 6.7 | 3,000 | 118 | Galv | 70,000 | 154,300 |
| ZCS3547 | ZCS3547-THI | 152 - 203 | 6 - 8 | 1,678 | 66 | Galv | 48,000 | 105,822 |
| ZCS12763 | ZCS12763-THI | 155 - 210 | 6.1 - 8.25 | 3,000 | 118 | Galv | 70,000 | 154,300 |
| ZCS12764 | ZCS12764-THI | 195 - 250 | 7.67 - 9.8 | 3,000 | 118 | Galv | 90,000 | 198,000 |
| ZCS3548 | | 203 - 255 | 8 - 10 | 2,047 | 80.5 | Galv | 60,000 | 132,277 |
| | ZCS3548-THI | 203 - 255 | 8 - 10 | 2,500 | 98.5 | Galv | 60,000 | 132,277 |
| ZCS12765 | ZCS12765-THI | 235 - 285 | 9.25 - 11.22 | 3,000 | 118 | Galv | 90,000 | 198,000 |
| ZCS3549 | | 255 - 305 | 10 - 12 | 1,945 | 76.5 | Galv | 60,000 | 132,277 |
| | ZCS3549-THI | 255 - 305 | 10 - 12 | 2,500 | 98.5 | Galv | 60,000 | 132,277 |
| ZCS3550 | ZCS3550-THI | 305 - 355 | 12 - 14 | 3,006 | 118.35 | Galv | 60,000 | 132,277 |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH



1 888 685 9478



sales@slingcoamerica.com