

OFFSET EYE SPLIT MESH ROD CLOSING CABLE SUPPORT GRIPS



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Supports cable in vertical or horizontal mode
- ✓ Use when the end of the cable is not accessible

Ideal for several support points along the same cable when the cable ends are not accessible. Made from 304 Stainless Steel.

Slingco Part No.	Approx. Break Load (lb)	Approx. Break Load (kg)	Lattice Length (in)	Lattice Length (mm)	Range (in)	Range (mm)
ZCS3031	500	225	7	178	0.50 - 0.63	12 - 16
ZCS3032	750	340	9	229	0.63 - 0.75	16 - 19
ZCS3033	950	430	10	254	0.75 - 1.00	19 - 25
ZCS3034	1,500	680	12	305	1.00 - 1.25	25 - 31
ZCS3035	1,500	680	14	359	1.25 - 1.50	31 - 38
ZCS3036	1,500	680	15	381	1.50 - 1.75	38 - 44
ZCS3037	2,000	905	16	406	1.75 - 2.00	44 - 50
ZCS3038	3,100	975	19	483	2.00 - 2.50	50 - 63
ZCS3039	3,100	975	20	508	2.50 - 3.00	63 - 76
ZCS3040	4,300	1,720	21	533	3.00 - 3.50	76 - 89
ZCS3041	4,900	1,720	21	533	3.50 - 4.00	89 - 102

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

- ☎ 1 888 685 9478
- ✉ sales@slingcoamerica.com