

MARINE CABLE GRIPS - SINGLE EYE



KEY FEATURES

- ✓ Bespoke design available
- ✓ Single, double, triple and quadruple weave depending upon requirement
- ✓ Thimble eye optional

These speciality grips, often called chinese fingers, are extremely heavy duty and suitable for large underwater pulling applications, plus others within the oil and gas industry. Galvanised steel construction for heavy duty pulling such as export cables, array cables, umbilicals and other underwater cable installations. Sizes handle cables ranging from 3.5" to over 14" diameter. Manufactured to order.



GET IN TOUCH



1 888 685 9478



sales@slingcoamerica.com

MARINE CABLE GRIPS - SINGLE EYE

Slingco Part No. FLEX Eye	Slingco Part No. THIMBLE Eye	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Lattice Material	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS12740-2M	ZCS12740-THI-2M	90 - 125	3.5 - 5	2,000	78.75	Galv.	50,000	110,230
ZCS12740-2.5M	ZCS740-THI-2.5M	90 - 125	3.5 - 5	2,500	98.5	Galv.	50,000	110,230
ZCS12740-3M	ZCS12740-THI-3M	90 - 125	3.5 - 5	3,000	118	Galv.	50,000	110,230
ZCS3525	ZCS3525-THI	102 - 127	4 - 5	2,005	78.75	Galv.	45,500	110,310
ZCS12741-2.5M	ZCS12741-THI-2.5M	110 - 145	4.3 - 5.7	2,500	98.5	Galv.	55,000	121,250
ZCS12741-3M	ZCS12741-THI-3M	110 - 145	4.3 - 5.7	3,000	118	Galv.	55,000	121,250
ZCS3526	ZCS3526-THI	127 - 152	5 - 6	1,821	71.7	Galv.	47,500	104,720
ZCS12742	ZCS12742-THI	130 - 172	5.1 - 6.7	3,000	118	Galv.	65,000	143,300
ZCS3527	ZCS3527-THI	152 - 203	6 - 8	1,678	66	Galv.	50,000	110,230
ZCS12743	ZCS12743-THI	155 - 210	6.1 - 8.25	3,000	118	Galv.	70,000	154,300
ZCS12744	ZCS12744-THI	195 - 250	7.67 - 9.8	3,000	118	Galv.	85,000	187,393
ZCS3528	ZCS3528-THI	203 - 255	8 - 10	2,047	80.5	Galv.	63,000	138,900
ZCS12745	ZCS12745-THI	235 - 300	9.25 - 11.81	3,000	118	Galv.	90,000	198,400
ZCS3529	ZCS3529-THI	255 - 305	10 - 12	1,945	76.5	Galv.	63,000	138,900
ZCS3530	ZCS3530-THI	305 - 355	12 - 14	2,460	97	Galv.	62,600	138,000

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

1 888 685 9478

sales@slingcoamerica.com