

BANDED CABLE PROTECTORS

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ Lightweight
- ✓ Low cost alternative
- ✓ Suitable for shallow wells or ones with minimal deviation

These lightweight, stamped steel protective cable guards offer a compact, low-cost alternative to our standard Cable Protectors. Designed for use in shallow wells with little to no deviation, the protectors are situated across the coupling and attached to the tubing string with steel bands.

Tubing Size	Cable Options	Material	Custom Configurations?
2 3/8" to 2 7/8"	.125" to .625" round or flat	Low Carbon Steel, SS	YES
3.5" - 4.5"	.125" to .75" round or flat	Low Carbon Steel, SS	YES
5.5 - 7.0"	.125" to 1.25" round or flat	Low Carbon Steel, SS	YES

Note

Contact Slingco with configuration requirements

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

☎ 1 888 685 9478

✉ sales@slingcoamerica.com