

# IN-VAULT BULL WHEELS

## **⚠ WARNING**

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Lightweight and portable
- ✓ Can be assembled on site by 1 person
- ✓ Can be used in underground vaults where there is limited vertical access

The Slingco In-Vault Bull Wheel can be dismantled and passed through a 3ft x 3ft access opening in the top of an underground vault. Available in 8ft and 6ft diameter sizes.

Slingco has developed an 8ft wheel for stringing cables around 180° within underground vaults.

The rotating wheel allows operators to impose a bend of up to Ø4 inches on conductor wire inside an underground concrete 'vault'.

Supplied with a two point wall fixing, the wheel is mounted on an upright post that allows height adjustment from approximately 1ft to 7ft from the ground. Interchangeable circumference sections provide further options depending on application needs.

Available in 6ft and 8ft diameter, the Slingco Bull Wheel can also be produced at different sizes to suit your application. The 6ft and the 8ft wheels are designed to withstand an imposed load of 8,000lb (SWL) with a factor of safety (FOS) of 3.



Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 1 888 685 9478

## GET IN TOUCH

☎ 1 888 685 9478

✉ [sales@slingcoamerica.com](mailto:sales@slingcoamerica.com)