

2K STRAP HOIST

⚠️ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ✓ ASME B-30-21 compliant
- ✓ 125% working load tested
- ✓ Hi-viz yellow strap
- ✓ Interlocking pawl lever system
- ✓ Replacement parts readily available
- ✓ Hot stick operable version

The Slingco 2K strap features a hi-viz yellow strap for easy identification. In single line mode capacity is 1K. When used in double line mode capacity is 2K. The 2k Strap Hoist has a pressure die cast drum for professional look and smooth finish to minimize the risk of strap fraying.

The strap hoist has three operating positions: lift/pull, lower/release, and freewheeling.

For information while in the field, use the QR code on Slingco products to quickly reach manual and helpful information on your mobile.

| Slingco Part No. | Type | Single Line Capacity lb (kg) | Single Line Lift ft (m) | Single Line Headroom in (mm) | Double Line Capacity lb (kg) | Double Line Lift ft (m) | Double Line Headroom in (mm) | Tool Weight lb (kg) |
|------------------|--------------------|------------------------------|-------------------------|------------------------------|------------------------------|-------------------------|------------------------------|---------------------|
| ZLH14321 | Standard | 1,000 (453.6) | 9 (2.7) | 15.5 (393.7) | 2,000 (907) | 4.25 (1.3) | 18.5 (469.9) | 8.46 (3.84) |
| ZLH14447 | Hot stick operated | 1,000 (453.6) | 9 (2.7) | 15.5 (393.7) | 2,000 (907) | 4.25 (1.3) | 18.5 (469.9) | 9.04 (4.10) |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

- ☎ 1 888 685 9478
- ✉ sales@slingcoamerica.com